DECLARATION OF PERFORMANCE

NO. MWUK/FL/213-004/CPR/DOP





1. PRODUCT-TYPE:

Solid softwood tongue & groove flooring

2. INTENDED USE OR USES:

Solid softwood tongue & groove flooring for internal use, to be mechanically fixed

3. MANUFACTURER:

Metsä Wood UK Ltd, Mayne House, Fenton Way, Southfields Business Park, Basildon. SS15 6RZ www.metsawood.com

Please visit www.metsawood.com/dop for DoPs online

5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:

(AVCP) System 4

6A. HARMONISED STANDARD:

EN 14342:2013



7. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	D fl s1	EN 14342:2013
Minimum mean density	500kg / m³ Pine (Pinus sylvestris) 440kg / m³ Spruce (Picea abies)	
Minimum overall thickness	18-28mm	
The end-use condition to be applied	With or without air gap underneath	
Emission (release) of formaldehyde	E1	
Content of pentachlorophenol	< 5 ppm	
Breaking Strength	NPD	
Slipperiness USRV	NPD	
Thermal conductivity	0,13 W/(m K) Pine 0,12 W/(m K) Spruce	
Biological durability (EN 350)	Class 4	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Michael Lomas Vice President, UK Upgrade Operations Metsä Wood UK Ltd

	Me
Widnes, 02.10.2014	

