



PPG Architectural Coatings EMEA

Region UK and Ireland

PPG Architectural Coatings UK Limited
HUDDERSFIELD ROAD,
BIRSTALL, BATLEY,
WEST YORKSHIRE WF17 9XA
UNITED KINGDOM
Telephone +44 (0) 1924 354000
Emergency Tel As above
Fax +44 (0) 1924 354533
E mail regulatoryaffairs@ppg.com

HEALTH AND SAFETY DATA SHEET

1. **PRODUCT:** LEYLAND TRADE Super Leytex High Opacity Matt
REVISION: 10
USE: A water-borne matt emulsion paint for interior walls and ceilings.
Application by brush, roller or spray.
- PAGE: 1 of 4
DATE: 1.02.10
2. **HAZARDS IDENTIFICATION**
The product is not classified as dangerous according to the CHIP Regulations. Also refer to section 11.
3. **COMPOSITION/INFORMATION ON INGREDIENTS**
Substances presenting a health or environmental hazard within the meaning of the CHIP Regulations or which are assigned Workplace Exposure Limits: -
- | Name | EC No | CAS No | Conc.Range | Symbol* | R-Phrases* |
|--|-------|--------|------------|---------|------------|
| The product does not contain any substances presenting a hazard within the meaning of the CHIP Regulations | | | | | |
- * for full text see section 16.
4. **FIRST AID MEASURES**
General: In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
Skin Contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or a recognised skin cleaner. DO NOT USE SOLVENT OR THINNERS.
Eye Contact: Remove contact lenses. Irrigate copiously with clean, fresh water, holding the eyelids apart and seek medical advice.
Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.
5. **FIRE FIGHTING MEASURES**
The liquid products are 'non-flammable'
Extinguishing Media:
Recommended: alcohol resistant foam, CO₂, powder, water spray/mist
Not to be used: water jet
Recommendations: Fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Appropriate self contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run off from fire fighting to enter drains or watercourses.
6. **ACCIDENTAL RELEASE MEASURES**
Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth, and place in a suitable container for disposal in accordance with the waste regulations (see section 13). Do not allow to enter drains or water courses. Clean preferably with a detergent; avoid use of solvents. If the product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in storage and use areas. For Occupational Exposure Controls measures see Section 8. Keep the container tightly closed. Never use pressure to empty, the container is not a pressure vessel. For Occupational Exposure Controls measures see section 8.

The Manual Handling Operations Regulations may apply to the handling of containers/packages of this product. To assist employers the following method of calculating the weight of any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the product in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

STORAGE: Observe label precautions. Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Keep out of the reach of children. Store separately from oxidising agents and strongly alkaline and strongly acidic materials. Containers which are opened should be properly resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE CONTROLS: Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant Exposure Limit Values, suitable respiratory protection must be worn (see 'Occupational Exposure Controls' below).

EXPOSURE LIMIT VALUES:

Substance	Exposure Limit Values				Notations
	8 hr LTEL (1)		15 min STEL (2)		
	ppm	mgm ⁻³	ppm	mgm ⁻³	
Particulates (Sprayed material): -					
Respirable	-	5(W)	-	-	-
Total inhalable	-	10(W)	-	-	-

(1) Long-Term Exposure Limit - 8 hour Time Weighted Average

(2) Short-Term Exposure Limit - 15 minute reference period

(W) Workplace Exposure Limit (WEL)

(SUP) Recommended by suppliers

(A) Allocated limits by analogy with similar materials

WEL's are taken from the current version of EH40, except those marked (SUP) which are assigned by the supplier of the substance

OCCUPATIONAL EXPOSURE CONTROLS: All Personal Protective Equipment, including Respiratory Protective Equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

RESPIRATORY PROTECTION: If exposure to hazardous substances identified above cannot be controlled by the provision of local exhaust ventilation and good general extraction, suitable respiratory protective equipment should be worn. Dry sanding of the dry film will give rise to dust and/or hazardous fumes.

HAND PROTECTION: When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect exposed areas of skin but are not substitutes for full protection. They should not be applied once exposure has occurred.

EYE PROTECTION: Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION: Cotton or cotton/synthetic overalls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a recognised skin cleaner. Regular skin inspection of users of this product is recommended. ALWAYS WASH YOUR HANDS BEFORE EATING, SMOKING OR USING THE TOILET.

9. PHYSICAL AND CHEMICAL PROPERTIES

physical state	pigmented viscous liquid
flash point	>100°C
specific gravity	1.33-1.36 @ 20°C
solubility in water	miscible
pH	7-9
boiling point	100°C
VOC Directive 2004/42/CE	Class A.a. Max VOC 15g/l

10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions (see section 7). In a fire, hazardous decomposition products such as smoke, carbon dioxide, carbon monoxide and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of an exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. The product has been assessed following the conventional method in CHIP and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. See sections 2 and 15 for details of the resulting hazard classification. Exposure to organic solvent vapours in excess of the stated Exposure Limit may result in adverse health effects such as irritation of the mucous membrane and respiratory system and adverse effects on the renal and central nervous system. Symptoms include headache, dizziness fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Splashes in the eye may cause irritation and reversible local damage. Repeated or prolonged contact may lead to removal of natural fats from the skin resulting in non allergic contact dermatitis.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. The requirements of regulations made under the Pollution Prevention and Control Act may apply to the use of this product. The product has been assessed following the conventional method in CHIP and is not classified as dangerous for the environment.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

The classification of this product, when disposed of as waste is 08 01 12. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information contact your local waste authority.

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under The Control of Pollution Act and The Environmental Protection Act. Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

14. TRANSPORT INFORMATION

Transport within the users premises: - Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Onwards transport subsequent to purchase: - Transport to be in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air.

Proper shipping name:	The product is not classified as dangerous for carriage
UN number:	
Hazard class:	
Packing Group:	
Sub-hazard class:	

15. REGULATORY INFORMATION

The product is determined as not being dangerous according to the CHIP Regulations. However, the following precautions should be observed: -

S Phrases

S2	Keep out of the reach of children
S23/42	Do not breathe vapour/spray, wear suitable respiratory protective equipment
S24/25	Avoid contact with skin and eyes
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28	After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner
S51	Ensure good ventilation during application and drying

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

16. OTHER INFORMATION

Symbols and text of the R phrases in section 3: -

-

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of the CHIP Regulations. The product should not be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and advice can be found in: -

The Control of Substances Hazardous to Health Regulations 2002 (SI2002:2677) and amendments
COSHH Essentials: easy steps to control chemicals (HSG193). Details of Control Guidance Sheets, which may be relevant to the particular conditions of use, can also be found in this publication.
Dangerous Substances and Explosive Atmospheres Regulations 2002 (SI 1992:2793)
ACoP - Dangerous Substances and Explosive Atmospheres Regulations 2002 (L138)
The Manual Handling Regulations 1992 (SI 1992:2793)
Chemical Warehousing: The Storage of Packaged Dangerous Substances (HSG51)
The Environmental Protection (Duty of Care) Regulations 1992 (SI 1992:2839)
A Guide to Working with Solvents (INDG 272)
HSE website www.hse.gov.uk