

DESCRIPTION

Johnstone's Trade Cleanable Matt is a tough premium matt emulsion that is designed to extend maintenance cycles through its excellent stain resistance and high durability. Designed for high traffic areas which require frequent cleaning it helps to prevent stains setting into the paint and makes removing stains and marks easier.

RECOMMENDED USES

Suitable for interior use on walls and ceilings.



TYPE OF SUBSTRATE

Suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations. Also suitable for primed wood and metal.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Matt.

VOLUME SOLID

38%

COVERAGE

Johnstone's Trade Cleanable Matt will cover up to 15 square metres per litre depending on the nature and porosity of the surface being painted.



FILM THICKNESS

Wet: 70µm, dry: 27µm.

DRYING TIME

Touch dry in 2 hours. Recoatable after 4 hours.



TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 10g/l VOC.



KEY PROPERTIES

- Stays matt after cleaning
- Super Durable
- Excellent stain resistance
- Ideal for high traffic areas

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces such as new plaster with a coat of Johnstone's Trade Cleanable Matt thinned up to 20% with clean water. Do not apply in temperatures below 10°C or in damp conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

CLEANING STAINS

Apply all-purpose cleaner to sponge or soft cloth and wipe away stain from surface and allow to dry.

SIZES

1 Litre, 2.5 Litre, 5 Litre & 10 Litre.