

Damp Block

A waterproofing undercoat that is able to mask both water stains and damp patches. Suitable for over coating with wallpaper, tiles or any emulsion paint from the Leyland Trade range for a choice of finish and colour.

Recommended uses

Interior ✓

Type of substrate

Interior walls and ceilings. For further information on substrates please contact Technical Advisory on 01924 354354.

Colour availability

White (2.5ltr & 750ml)

Finish

Matt

Volume solid

Please contact Technical Advisory on 01924 354354 to obtain this information.

Coverage

1 litre will cover between approximately 8 and 12 square metres depending on the nature and porosity of the surface being painted.

Drying time

Touch-dry: approx. 6 hours. Between coats: approx. 12 hours. The drying time on some surfaces during the winter season may be longer.

Transportation and storage

PROTECT FROM FROST. To avoid the risk of spillage, always store and transport in a secure upright position. Lift with care - gross weight does not exceed 4 kilograms. (2.5L). Do not use empty container for storing food.

VOC content

LOW VOC CONTENT 0.3-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 10g/l VOC.

Film thickness

Wet: 125 micron. Dry: Please contact Technical Advisory on 01924 354354 to obtain this information.

Preparation

All surfaces to be painted must be clean, sound and free from dust. Can be applied to damp but not dripping walls. Remove all loose and defective paint. Brush, scrape and/or remove dust from the surface. Examine all old surfaces prior to application in order to determine the nature of the preparation required. For further advice please contact Technical Advisory on 01924 354354.

On dry rough plaster or similar surfaces: Brush and remove dust from the surface.

On very damp rough plaster or similar surfaces: Seal first with a single coat, do not thin.

On porous or powdery surfaces: Stabilise surfaces of a highly porous or friable nature with a Leyland Trade Stabilising Damp Treatment as directed.

On old surfaces or damaged paintwork: Rub down or strip and remove all loose and flaking material then examine the surface prior to application in order to determine the nature of the preparation required.

Application

Stir well before use. Apply evenly by brush or roller and avoid overspreading.

Please note: A temperature of > 10°C and a relative humidity of < 80% is necessary for optimal drying.

Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Contains 1,2-benzisothiazol-3(2H)-one, 3-iodo-2-propynyl butylcarbamate and 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.