

PAINT TO BE PROUD OF

# DESCRIPTION

Johnstone's Advanced Stain Block Primer is a heavy duty, shellac based coating designed to block out difficult stains. Ideal for sealing tar, bitumen and creosoted surfaces and to prevent bleeding through in subsequently applied solvent based paints. Can also be used as a quick drying white line paint.

#### **RECOMMENDED USES**



Primer and sealer for timber, wood composites, plaster, cement and brickwork. Seals tar, bitumen, creosoted areas.

# SPECIAL PROPERTIES

Heavy stain blocking. Rapid drying. Can also be used as a quick drying white line paint.

#### COLOUR RANGE

Brilliant White.

# FINISH

Matt.

VOLUME SOLID



COVERAGE



Johnstone's Advanced Stain Block Primer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

# DRYING TIME



Touch dry in 10 minutes. Recoatable after 30 minutes.

# **TRANSPORTATION & STORAGE**

To avoid the risk of spillage always store and transport in a secure upright position. STORE AWAY FROM HEAT AND FLAME.

# THINNER

Mineralised Methylated Spirit.

#### VOC CONTENT

HIGH VOC CONTENT 25-50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 500g/l VOC.

# FILM THICKNESS

Wet: 100µm, dry: 25µm.

SIZE

2.5 Litre.



All surfaces should be clean, dry and free from oil, grease and loose and flaking material.

#### **APPLICATION**



Advanced Stain

**Block Primer** 

Stir well before use. Suitable for application by brush or roller. Apply a full coat, freely and smoothly with the minimum of brushwork. If a second coat is required, this can be applied after approximately 30 minutes. Avoid over-brushing.

#### CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with Mineralised Methylated Spirit. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

#### PRECAUTIONS

- Danger
- Highly flammable liquid and vapour.
- Safety data sheet available on request.
- · Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations
- Do not get in eyes, on skin, or on clothing.
- Wear protective gloves and eye or face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.



PAINT TO BE PROUD OF

For further information and advice please call 01924 354354 Find out more at: www.johnstonestrade.com