# SAFETY DATA SHEET

Date of issue/Date of revision : 4 August 2016 Version : 1.03



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

Product code : 17000DUP026
Other means of : Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Consumer applications, Professional applications, Used by spraying.

Use of the substance/ : Coating.

mixture

1.3 Details of the supplier of the safety data sheet

PPG Architectural Coatings UK Ltd Huddersfield Road Birstall, West Yorkshire WF179XA United Kingdom +44 (0) 1924 354000

Fax: +44 (0) 1924 354533

e-mail address of person responsible for this SDS

: regulatoryaffairs@ppg.com

1.4 Emergency telephone number

**Supplier** 

**Telephone number** +44 (0) 1924 354000

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : No signal word.

English (GB) United Kingdom (UK) 1/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## **SECTION 2: Hazards identification**

**Hazard statements**: Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

General : Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

**Prevention**: Avoid release to the environment.

Response : Collect spillage.
Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

P102, P101, P273, P391, P501

**Hazardous ingredients** 

Supplemental label

elements

: Not applicable.

: Not applicable.

: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

**Special packaging requirements** 

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

			<u>Classification</u>	
Product/ingredient name	Identifiers	% by weight	Regulation (EC) No. 1272/2008 [CLP]	Туре
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≥1.0 - ≤5.0	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
propane-1,2-diol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≥1.0 - ≤5.0	Not classified.	[2]
(2-methoxymethylethoxy)propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≥1.0 - ≤5.0	Not classified.	[2]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤1.0	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
ammonia	REACH #: 01-2119982985-14 EC: 215-647-6	≤0.30	Skin Corr. 1B, H314 Eye Dam. 1, H318	[1]

English (GB) United Kingdom (UK) 2/14

## **SECTION 3: Composition/information on ingredients**

		•		
	CAS: 1336-21-6 Index: 007-001-01-2		STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	
bronopol (INN)	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.090	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10)	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## 4.2 Most important symptoms and effects, both acute and delayed

## Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** : No known significant effects or critical hazards.

## Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

English (GB) United Kingdom (UK) 3/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## SECTION 4: First aid measures

**Skin contact** : Adverse symptoms may include the following:

> irritation dryness cracking

Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

# **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides

### 5.3 Advice for firefighters

fighters

Special precautions for fire- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

English (GB) United Kingdom (UK) 4/14 Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## **SECTION 6: Accidental release measures**

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

## 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Storage temperature: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

**Recommendations**: Not available.

English (GB) United Kingdom (UK) 5/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## **SECTION 7: Handling and storage**

**Industrial sector specific** : Not available.

solutions

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 8.1 Control parameters

## Occupational exposure limits

Product/ingredient name	Exposure limit values
propane-1,2-diol	EH40/2005 WELs (United Kingdom (UK), 12/2011).
	TWA: 10 mg/m³ 8 hours. Form: Particulate
	TWA: 150 ppm 8 hours. Form: Sum of vapour and particulates
	TWA: 474 mg/m <sup>3</sup> 8 hours. Form: Sum of vapour and particulates
(2-methoxymethylethoxy)propanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed
3 3 3 3 7 1	through skin.
	TWA: 308 mg/m <sup>3</sup> 8 hours.
	TWA: 50 ppm 8 hours.

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## **DNELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
(2-methoxymethylethoxy)propanol	DNEL	Long term Inhalation	308 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	37.2 mg/m³	Consumers	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	Consumers	Systemic
zinc oxide	DNEL	Long term Inhalation	5 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Oral	0.83 mg/ kg bw/day	Consumers	Systemic
	DNEL	Long term Dermal	87 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Dermal	87 mg/kg bw/day	Workers	Systemic

English (GB) United Kingdom (UK) 6/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## **SECTION 8: Exposure controls/personal protection**

#### **PNECs**

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
(2-methoxymethylethoxy)propanol	-	Fresh water	19 mg/l	Assessment Factors
	_	Marine water	1.9 mg/l	Assessment Factors
	-	Sewage Treatment	4168 mg/l	Assessment Factors
	_	Fresh water sediment	70.2 mg/kg	Equilibrium Partitioning
	_	Marine water sediment	7.02 mg/kg	Equilibrium Partitioning
	_	Soil	2.74 mg/kg	Equilibrium Partitioning
zinc oxide	-	Fresh water	20.6 μg/l	Sensitivity Distribution
	_	Marine water	6.1 µg/l	Sensitivity Distribution
	-	Fresh water sediment	117 mg/kg dwt	Sensitivity Distribution
	-	Sewage Treatment	52 μg/l	Assessment Factors
		Plant		
	-	Marine water sediment	56.5 mg/kg dwt	Assessment Factors
	-	Soil	35.6 mg/kg dwt	Sensitivity Distribution

## 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

## **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

Hand protection

- : Safety glasses with side shields.
- Ehemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

**Gloves** 

: For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

English (GB) United Kingdom (UK) 7/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## SECTION 8: Exposure controls/personal protection

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Filter type: organic vapour (Type A) and particulate filter P3

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour : White. **Odour** : Faint odour. **Odour threshold** : Not available.

pН 8.8

: Not available. Melting point/freezing point : 100°C

Initial boiling point and boiling

range

Flash point

: Closed cup: Not applicable. [Product does not sustain combustion.]

**Evaporation rate** : Not available.

Material supports combustion. : No.

Flammability (solid, gas) : Not available. Upper/lower flammability or : Upper: 0%

explosive limits

Vapour pressure : Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted

average: 2.88 kPa (21.6 mm Hg) (at 20°C)

Vapour density Highest known value: 5.1 (Air = 1) ((2-methoxymethylethoxy)propanol).

Weighted average: 3.67 (Air = 1)

1.26 **Relative density** 

: Partially soluble in the following materials: cold water. Solubility(ies)

Partition coefficient: n-octanol/ : Not available.

: Not applicable. **Auto-ignition temperature Decomposition temperature** : Not available.

**Viscosity** : Kinematic (40°C): >0.21 cm<sup>2</sup>/s

**Explosive properties** : Not available. **Oxidising properties** : Not available.

#### 9.2 Other information

No additional information.

English (GB) **United Kingdom (UK)** 8/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous** : Decomposition products may include the following materials: carbon monoxide,

**decomposition products** carbon dioxide, smoke, oxides of nitrogen.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LD50 Oral	Rat	>11 g/kg	-
Kaolin	LD50 Oral	Rat	>5000 mg/kg	-
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
(2-methoxymethylethoxy) propanol	LC50 Inhalation Vapour	Rat	500 ppm	4 hours
	LD50 Dermal	Rabbit	9.5 g/kg	-
	LD50 Oral	Rat	5.23 g/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-
bronopol (INN)	LC50 Inhalation Vapour	Rat	800 mg/m <sup>3</sup>	4 hours
•	LD50 Dermal	Rat	64 mg/kg	-
	LD50 Oral	Rat	180 mg/kg	_

**Conclusion/Summary**: Not available.

**Acute toxicity estimates** 

Route	ATE value
Not available.	

**Irritation/Corrosion** 

**Conclusion/Summary**: Not available.

**Sensitisation** 

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

**Reproductive toxicity** 

**Conclusion/Summary**: Not available.

English (GB) United Kingdom (UK) 9/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

# **SECTION 11: Toxicological information**

**Teratogenicity** 

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ammonia	Category 3	Not applicable.	Respiratory tract irritation
bronopol (INN)	Category 3	Not applicable.	Respiratory tract irritation

## Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on likely

routes of exposure

: Not available.

### Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No specific data.Ingestion: No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

**Eye contact** : No specific data.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

## Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.

English (GB) United Kingdom (UK) 10/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## SECTION 11: Toxicological information

Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Other information : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide trizinc bis(orthophosphate)	Acute LC50 >100 mg/l Fresh water Acute LC50 0.112 mg/l Chronic NOEC 0.026 mg/l	Daphnia - Daphnia magna Fish Fish	48 hours 96 hours 30 days
zinc oxide	Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - Daphnia magna - Neonate	72 hours 48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propane-1,2-diol	-0.92	-	low
bronopol (INN)	0.18		low

## 12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

English (GB)	United Kingdom (UK)	11/14
--------------	---------------------	-------

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## **SECTION 12: Ecological information**

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

#### **Packaging**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging		European waste catalogue (EWC)
Container	15 01 02	plastic packaging
Container	15 01 04	metallic packaging

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# 14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate))
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

English (GB) United Kingdom (UK) 12/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

# 14. Transport information

Marine pollutantNot applicable.Not applicable.(trizinc bis substances)Not applicable.

#### **Additional information**

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Tunnel code : (E

ADN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The product is only regulated as an environmentally hazardous substance when transported in tank

vessels

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture,

placing on the market and

use of certain dangerous

substances, mixtures and

articles

**Mixture** 

**Other EU regulations** 

**VOC for Ready-for-Use** 

: IIA/i. One-pack performance coatings. EU limit values: 140g/l (2010.)

This product contains a maximum of 100 g/l VOC.

**Seveso Directive** 

This product is controlled under the Seveso Directive.

#### **Danger criteria**

#### Category

E2: Hazardous to the aquatic environment - Chronic 2

C9ii: Toxic for the environment

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

English (GB) United Kingdom (UK) 13/14

Code : 17000DUP026 Date of issue/Date of revision : 4 August 2016

JOHNSTONES PERFORMANCE Advanced Multi Surface Primer

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/20081

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

## Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aquatic Chronic 2, H411	Calculation method	

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

## Full text of classifications [CLP/GHS]

Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Aquatic Acute 1, H400	ACUTE AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410	LONG-TERM AQUATIC HAZARD - Category 1
Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 2
Eye Dam. 1, H318	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Skin Corr. 1B, H314	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
	(Respiratory tract irritation) - Category 3

#### <u>History</u>

Date of issue/ Date of : 4 August 2016

revision

Date of previous issue : 28 June 2016

Prepared by : EHS Version : 1.03

## **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) United Kingdom (UK) 14/14