

## DESCRIPTION

Johnstone's Advanced Multi-Surface Primer is a high performance, anti-corrosive, low odour, water based primer. It has been specially formulated to provide outstanding adhesion over a variety of difficult to adhere to surfaces including, ceramic tiles, galvanised steel, aluminium, melamine and MDF. It also has good anti-corrosive properties making it ideal for use on ferrous metals. It can be overcoated with any Johnstone's Trade undercoat and topcoat. Complies with ISO12944-2:C2-C3 for Atmospheric Corrosivity - suitable for use in urban and industrial atmospheres with moderate sulphur dioxide pollution.

## RECOMMENDED USES



Int/Ext icon - Primes new galvanised metal, melamine, powder coat, glazed tiles, matt tiles, quarry tiles, glass and suitably prepared ferrous and non-ferrous metals.

## COLOUR RANGE

White.

## FINISH

Matt

## VOLUME SOLID

48.2%

## COVERAGE



Johnstone's Advanced Multi-Surface Primer will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface.

## DRYING TIME



Under normal conditions, touch dry in 1-2 hours and recoatable after 4 hours. Ensure good ventilation during application and drying.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 4 kilograms. (2.5L) (8kg for 5L)

Do not use empty container for storing food. (not 1lt)

## Cleaner

Water

## VOC CONTENT

MEDIUM VOC CONTENT 8-24.99% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i):140g/l (2010).

This product contains max 100g/l VOC.

## FILM THICKNESS

wtf 90mic , dft 43mic

## SIZE

1ltr and 5ltr

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material, dirt, grease or other surface contaminants. Any existing rust or millscale should be removed. Certain surfaces, such as new galvanised metal, should be cleaned with Johnstone's Cleaner & Degreaser and then lightly sanded with a fine waterproof abrasive paper and wiped clean. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

## APPLICATION



Stir well before use. Easy to apply by brush or roller. Do not apply in temperatures below 8°C or externally when rain is imminent.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

### PAINT PRODUCT

- Toxic to aquatic life with long lasting effects.
- Contains: 1,2-benzisothiazol-3(2H)-one.
- May produce an allergic reaction.
- Safety data sheet available on request.
- Avoid release to the environment.
- Collect spillage.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes.
- Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

