

DESCRIPTION

Johnstone's Eggshell is a premium quality, alkyd based mid sheen finish formulated for interior use on wood and metal surfaces. It provides a smooth, even surface that is washable and resistant to condensation.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Wood and metal.

Do not use over large surface areas.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Mid sheen.

VOLUME SOLID

61%

COVERAGE



Approximately 18-20 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME*



Recoat after 16–24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

High VOC content 25–50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.

FILM THICKNESS

Wet: 50µm, dry: 31µm.

SIZES

500ml, 1 Litre, 2.5 Litre, 5 Litre.

KEY PROPERTIES

- A solvent-based mid sheen finish for interior use on wood and metal.
- Resistant to condensation.
- Produces a smooth, washable, hard wearing finish.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's primer. Rub down previously painted surfaces fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **FLAMMABLE**
- Contains 2-butanone oxime. May produce an allergic reaction.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.