

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE DOP GP200

1 Identification Code: Bond-It GP200 General purpose Silicone

2. Batch Identification: By batch number – see print on packaging

3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and

Interior Use. **S1** Sanitary sealant

4. Manufacturer: Seal It Services t/a Bond It

Unit G16 River Bank Way Lowfields Business Park

Elland

West Yorkshire

HX5 9DN

5. Authorised Representative: Not applicable

6. System of assessment and Verification of

constancy:

System 3

7. Notified Body: NB01213

8. European Technical Assessment: Not Applicable

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD	
Reaction to Fire	Class E		
Release of Chemicals	None	See MSDS	
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,3:2012	
Resistance to Flow	≤3mm	Conditioning method A	
Loss of Volume	≤30%	Tested on aluminium with	
Tensile properties after water	NF	primer, glass without primer	
immersion			
Durability	Pass		
Microbiological Growth	S1		

^{10.} The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

PRadiona

Phil Radford Technical Manager Elland 26 June 2014