

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE DOP BDGIST

1 Identification Code: Bond-It Gist Silicone

2. Batch Identification: By batch number – see print on packaging

3. Intended uses: F EXT-INT Façade Sealant for Exterior and Interior Use

25LM. **G 25LM** Glazing Sealant 25LM. **XS1** Sanitary Sealant. **PW EXT_INT** Sealant for exterior and interior Pedestrian Walkways **CC** suitable for cold climates

4. Manufacturer: Seal It Services t/a Bond It

Unit G16 River Bank Way Lowfields Business Park

Elland

System 3

West Yorkshire, HX5 9DN

5. Authorised Representative: Not applicable

6. System of assessment and Verification of

constancy:

7. Notified Body: 0757

8. European Technical Assessment: Not Applicable

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2,3,4:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤10%	Tested on Mortar M1 without
Tensile properties at maintained	Pass	primer, Glass without primer,
extension		Aluminium without primer
Tensile Properties – secant	<0.9MPa	
modulus		
Adhesion/cohesion at variable	Pass	
temperature		
Adhesion/cohesion after water	Pass	
immersion.		
Adhesion/cohesion after	Pass	
exposure to heat, water and		
artificial light		
Microbiological Growth	XS1	
Elastic Recovery	>70%	
Tear Resistance	Pass	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

PROJEND

Phil Radford Technical Manager Elland 26 June 2014