

SAFETY DATA SHEET

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

Product: HYLOAD ORIGINAL DPC

Product Use: Damp proof course

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hyload Original DPC is manufactured from a blend of ingredients including coal tar pitch, synthetic polymers, mineral fillers, natural and synthetic fibres. Coal tar pitch volatiles have an occupational exposure limit, 8-hour TWA, of 0.14 mg/m³. However, as the volatiles are probably only likely to be released if the product temperature exceeds 200°C, there is no risk under normal working conditions. It is not classified as dangerous under the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP 3).

3. HAZARDS IDENTIFICATION

The product is not hazardous to health.

4. FIRST-AID MEASURES

IN ALL CASES IF SYMPTOMS ARE SEVERE, PERSIST OR CAUSE CONCERN, OBTAIN IMMEDIATE MEDICAL ADVICE.

First aid procedures apply when the product is subjected to high temperatures, e.g. in a fire, or when heated during installation.

Skin/Eyes: Not applicable under normal working conditions.

Inhalation: Not applicable under normal working conditions. In the event of a fire, remove from fumes to fresh air if any ill effects are experienced. Rest and keep warm.

5. FIRE-FIGHTING MEASURES

The product is difficult to ignite but in the presence of a flame will burn releasing harmful products. In the event of a fire, wear protective clothing. In confined areas wear self-contained breather apparatus. Extinguish fire with foam or dry powder.

6. ACCIDENTAL RELEASE MEASURES

Not applicable.

7. HANDLING AND STORAGE

Store under cover away from sources of heat and ignition. Refer also to product technical literature for any specific conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

See Section 2 for Occupational Exposure Limits (OEL). No particular handling precautions are necessary in normal use but the wearing of pvc gloves is recommended and good hygiene measures should be followed at all times.

9. **PHYSICAL AND CHEMICAL PROPERTIES**

The product is intended for use as a damp-proof course or part of a damp-proof course system in masonry walls. Additional product information including details of physical characteristics and application is available in the product technical literature.

10. **STABILITY AND REACTIVITY**

No known hazard.

11. **TOXICOLOGICAL INFORMATION**

No known hazard

12. **ECOLOGICAL INFORMATION**

No data available.

13. **DISPOSAL CONSIDERATIONS**

Dispose of waste material in accordance with national and local regulations.

14. **TRANSPORT INFORMATION**

Not classified for Road, Rail, Sea or Air Transport.

15. **REGULATORY INFORMATION**

Not classified as dangerous for supply under the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP 3).

16. **OTHER INFORMATION**

Revision Comments: This issue replaces RSDS 106, Revision Issue No.4 : July 2002.
Section amended: 1, 16.

Other products

Full product literature is available as downloads from our website www.ruberoid.co.uk or on request by email:
marketing@ruberoid.co.uk

Ruberoid Building Products

Literature Enquiries

E-Mail: marketing@ruberoid.co.uk Website: www.ruberoid.co.uk

Customer Services

Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB
Tel: 0800 028 5573 Fax: 0800 013 5574 E-Mail: sales@ruberoid.co.uk

Technical & Design Services

Coney Green Road, Clay Cross, Chesterfield, S45 9HZ
Tel: 0844 412 7228 Fax: 0844 412 7229 E-Mail: technical@ruberoid.co.uk

REVISION ISSUE No.5 : JANUARY 2005

The information contained in this data sheet does not constitute an assessment of workplace risk as required by current legislation. Whilst every care is taken to see that the information is correct and up to date, it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded