

WATER GEM INFORMATION SHEET

Codes	WG03, WG06	
Description	An in-line filters, containing granular activated carbon and scale inhibitor. Can be used in a wide variety of point of use applications, where the water supply is moderately hard. 3/8" spigot (inlet / outlet).	
Construction	Filter Casing Internal Grilles Reticulated Foam Particulate Filters Media Infill Connectors	Polypropylene Polypropylene Polyurethane Polyester G.A.C. (0.1% Ag) / Polyphosphate See above
Approvals	WRAS - 1303028	
Application	The filter is designed to reduce tastes and odours (including chlorine / chlorine by-products), THM's, PAH's, pesticides such as Simazine, Atrazine, Lindane, Dieldrin and inhibit the precipitation of scale deposits.	
Capacity	The filter is rated at 6000 ltr / six months (whichever is sooner).	
Flow Rate	The filter has a maximum recommended flow rate of 4.0 lpm	
Temperature Range	1 – 38°C (34 – 100°F)	
Pressure Range	0.5 – 8.6 bar (7.5 – 125psi)	
Dimensions	315mm x 50mm (max) – 3/8" smooth spigot	

Do not subject the filter to excessive pressure / water hammer. A wide range of control devices is available from your supplier. Only use on water supplies of a wholesome nature. Install in accordance with local bylaws. This information is provided as guidance only. Actual performance of a filter will depend upon the age of the unit and site conditions.