TECHNICAL DATA SHEET



CHEER ELECTRIC SHOWERS Cheer 8.5kW / 9.5kW

Product Specification

CHE85 W / CHE95 W **Product Code:**

Finish: White

Contemporary Product Type: Construction: Plastic (ABS)

Supply: Suitable for mains cold feed only Inlet Connections: 15mm push fit, 5 directional options

Outlet Connections:

Min 0.7bar, Max 10.0bar Working Pressures:





Additional Information

- Instantaneous electric shower drawing water direct from the mains supply; ideal for installations without stored hot water and second bathrooms.
- Consistent showering temperature is provided. The temperature stabilising device compensated for changes in the water pressure caused by other household fittings.
- Safety devices include thermal cut out & pressure relief.
- 3 Power settings. (Cold, Warm/Eco, Hot) and a separate temperature control.
- On/Off is operated by a rotary dial, ensuring temperature setting remains unaffected after each use.
- Push fit swivel inlet elbow pipe connection, enabling plumbing from 5 different directions.
- This shower is supplied with an adjustable riser kit and single mode rub-clean handset, 1.5m shower hose & hose retainer.
- Adjustable riser comes complete with adjustable bottom bracket so ideal to cover existing riser holes and tile
- Incorporates a temperature control device (TCD) that activates when the temperature is too high & the water inside the heater gets too hot. The TCD will switch off the power to the heating elements and once the unit cools down to a safe temperature, will come on again.







TECHNICAL DATA SHEET



Technical Advice: For further information please call 0844 7016273 or email

<u>customercare@bristan.com</u>

Guarantee: 2 years covering manufacturing faults.

Compliance / Approvals

BEAB safety: IWH 0759

BEAB EMC: IWH 0763

CE Mark: (**E**

Flow Rates (litres per minute)

System Pressure	8.5kW	9.5kW
Maximum Flow @ 40°C	4.0	4.5







