

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

ALUMINIUM PAINT CLP

Revision 0
Revision date 2015-03-04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	ALUMINIUM PAINT CLP
---------------------	---------------------

1.3. Details of the supplier of the safety data sheet

Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk

1.4. Emergency telephone number



Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri
-----------------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC	Xn; R65 R10 Symbols: Xn: Harmful.
Main hazards	Flammable. Harmful: may cause lung damage if swallowed.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304;

2.2. Label elements

Hazard pictograms	 
Signal Word	Danger
Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Precautionary Statement: Prevention	P210 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

ALUMINIUM PAINT CLP

Revision 0

Revision date 2015-03-04

2.2. Label elements

Precautionary Statement: Response	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use for extinction.
Precautionary Statement: Storage	P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7		30 - 40%	Xn; R65

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7		30 - 40%	Asp. Tox. 1: H304;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause dermatitis. May cause irritation to skin.
Ingestion	Harmful if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

ALUMINIUM PAINT CLP

Revision 0

Revision date 2015-03-04

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection**8.2. Exposure controls**

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
--	--

8.2.2. Individual protection measures	Wear chemical protective clothing.
--	------------------------------------

Eye / face protection	Approved safety goggles.
------------------------------	--------------------------

Skin protection - Handprotection	Chemical resistant gloves (PVC).
---	----------------------------------

Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.
-------------------------------	---

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

State	Liquid
Colour	Black
Odour	Aromatic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Boiling point	No data available
Flash point	38 °C
Evaporation rate	No data available
Flammability limits	No data available
Autoignition temperature	No data available
Explosive	No data available
Vapour pressure	No data available
Relative density	No data available
Partition coefficient	No data available
Viscosity	No data available
Vapour density	No data available
Fat Solubility	No data available
Vapour Flammability	No data available
Solubility	Insoluble in water

9.2. Other information

ALUMINIUM PAINT CLP

Revision 0

Revision date 2015-03-04

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of risk phrases in Section 3

R65 - Harmful: may cause lung damage if swallowed.

Text of Hazard Statements in Section 3

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.