

Repair Membrane

A polyester fibre membrane to pack and repair large cracks, fractures and breaks in joints connections. Use in conjunction with Leyland Trade Roof Repair and Waterproofer to provide a waterproof seal solution. Suitable for use on: Tiles, slates, zinc, galvanized sheets, concrete, fibre cement, bituminous coatings. Roofing, gutters and other exterior non-trafficable areas.

Recommended uses

Exterior ✓

Type of substrate

Tiles, slates, zinc, galvanised sheets, concrete, fibre cement, bituminous coatings. Roofing, gutters and other exterior non-trafficable areas. For further information on substrates please contact Technical Advisory on 01924 354354.

Coverage/Size availability

10m x 9cm and 10m x 18cm

Finish

N//A

Volume solid

N/A

Drying time

Leave to dry for 24 hours. Apply 1 coat of undiluted Leyland Trade Repair and Waterproofer at approx. 750ml/m² - leave for 24 hours between coats.

Transportation and storage

STORE AWAY FROM FROST.

VOC content

N/A

Film thickness

N/A

Preparation

Use in conjunction with Leyland Truguard Roof Repair and Waterproofer. All surfaces must be clean, dry, sound and free from dust. Remove any loose and defective paint then brush, scrape and remove dust from the surface. Strip the surface if necessary. Remove any moss, algae or mould with an appropriate fungicidal wash, all surfaces must be clean and dry and free from grease. Prime any metal surfaces with Leyland Trade Anti Corrosive Primer.

For further advice contact Technical Advisory on 01924 354354.

Application

Not recommended for use on cracks larger than 2mm wide and 10mm deep.

For widespread/large cracks. Cut the size required to cover the repair. Open the crack to a maximum 10mm wide and 15mm deep, then clean well removing any dust or impurities. Seal the crack with Leyland Trade All Weather Sealant then smooth with a spatula – pressing down to ensure that the sealant adheres to the edges and leave to dry. Liberally apply 1 coat of undiluted Leyland Trade Repair and Waterproofer on and around the affected area. Immediately apply Leyland Trade Repair Membrane with a brush or spatula, soaking it in the area and cover well (for this application, use approx. 1L/m²). Do not use on wet surfaces. Only apply Leyland Truguard Roof Repair and Waterproofer in temperatures between 5°C and 35°C. **For the repair of small cracks (less than 1mm) application use only Leyland Truguard Repair and Waterproofer. Take all the necessary precautions when working at height.**

Cleaning

Clean any equipment immediately after use with warm soapy water. Some local authorities have special facilities for disposal of waste coatings. Do not empty any products into drains or watercourses.

Warning

- Safety data sheet available on request.
- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.