

## Ready Mixed Crack Repair

A thick, flexible resin based coating reinforced with fibres. The added fibres interlace and strengthen the coating by filling and bridging gaps and cracks. Ready to use, flexible repair solution reduces handling for difficult to reach areas. Designed for maintenance, repair and waterproofing of most type of roof surfaces it is suitable for use on ridges, edges, channels, chimney stacks, parapets and flashings, surfaces made from cement, concrete, fibre cement, tile, slate and zinc.

### Recommended uses

Exterior ✓

### Type of substrate

Most roof surfaces including cement, concrete, fibre cement, tile, slate and zinc. For further information on substrates please contact Technical Advisory on 01924 354354.

### Colour availability

Terracotta and Black (2.5ltr)

### Finish

Matt

### Volume solid

42%

### Coverage

1 litre will cover approximately 1 to 2.5 square metres depending on the nature and porosity of the surface.

### Drying time

Touch dry in approximately 6 hours. Leave 24 hours between coats.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 4 kilograms.

Do not use empty container for storing food.

### VOC content

LOW VOC CONTENT 0.3-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/c): 40g/l (2010).

This product contains max 5g/l VOC.

### Film thickness

>200µm dry film

### Preparation

All surfaces to be painted must be clean, dry and free from grease. Remove all loose and defective paint. Brush, scrape and/or remove dust from the surface. Remove any moss, algae or mould with an appropriate fungicidal wash and degrease the surface with the aid of a suitable cleaner and degreaser.

Not for use on flat roofs.

Examine all old surfaces prior to application in order to determine the nature of the preparation required. For further advice contact Technical Advisory on 01924 354354.

**On rough surfaces:** Brush and remove dust from the surface. Remove any moss, algae or mould using an appropriate fungicidal wash.

**On powdery surfaces:** First treat with Leyland Trade Stabilising Damp Treatment as directed.

**On painted surfaces or old bituminous coatings:** Remove all loose and flaking material. Strip if necessary, then proceed as you would for rough surfaces.

**On metal surfaces:** Brush to remove all traces of rust then prime with Leyland Trade Anti-Corrosive Metal Primer.

**On galvanised surfaces:** Remove any traces of grease with a suitable cleaner and degreaser.

### Application

Stir well before use and apply by brush or roller. For optimal drying a temperature of >10°C and a relative humidity of <80% is necessary. Touch dry in approximately 6 hours. Leave approximately 24 hours between coats. Drying time on some surfaces during winter may be longer.

**For small cracks or cracks of less than 1mm:** Apply 2 coats of Leyland Truguard Ready Mixed Crack Repair at approx. 1kg/m<sup>2</sup> per coat, leaving 24 hours between coats.

**For widespread cracks or cracks of 1mm or above please use Leyland Trade Roof Repair and Waterproofer and Leyland Trade Repair Membrane. Take all the necessary precautions when working at height.**

### Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### Warning

• **May cause an allergic skin reaction.**

• Hazardous ingredients: 4,5-dichloro-2-octyl-3(2H)-isothiazolin-3-one.

• Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1) and 1,2-benzisothiazol-3(2H)-one.

• May produce an allergic reaction.

• Safety data sheet available on request.

• If medical advice is needed, have product container or label at hand.

• Keep out of reach of children.

• Dispose of contents/container to a waste disposal site in accordance with local/national regulations.

• Ensure good ventilation during application and drying.

• Do not get in eyes, on skin, or on clothing.

• Wear protective gloves and eye/face protection.

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

• IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.

• IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

