

Declaration of Performance

Revision 1

Product/DoP Ref: 034CPR13

Product-type: L9


Product intended to be used in walls and partitions

Manufacturer	Notified Body
<p>IG (Lintels) Ltd., Ballyreagh Business Park, Cookstown, Northern Ireland, BT80 9DG</p>	<p>Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ</p>
<p>IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type L9 is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003.</p>	<p>Ceram No. 1289, conducted determination of the product –type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003. The AVCP for the product is system 3.</p>

Essential characteristics	Lintel length (mm)			hEN
	0600-1500	1650-1800	1950-2700	
Load Bearing Capacity (kN) <i>Load Ratio 3:1</i>	NPD	NPD	NPD	EN 845-2: 2003
Load Bearing Capacity (kN) <i>Load Ratio 19:1</i>				
<i>Figures shown are safe working loads</i>	NPD	NPD	NPD	
Deflection Under Load	Less than Effective Span/325 at maximum safe working load			
Mass Per Unit Area	NPD			
Water Absorption	Zero			
Thermal Resistance (W/mK)	50			
Resistance to Fire	NPD (Contact IG Technical Department for information)			
Durability (against corrosion)	L14			
Durability (against freeze/thaw)	Resistant			
Dangerous Substances	None			

Date: 14/06/2013

Issued under the sole responsibility of IG Lintels, signed by:



Sean Coyle (CEO)