

Declaration of Performance

Declaration Number: A0008-00-EN

ANCON hereby declares that the product range identified as,

Staifix HRT4 200mm

conforms to the provisions of,

ZA Annex, EN 845-1: 2003 +A1: 2008

as a

Symmetrical Wall Tie covered in clause 1 of the standard

Intended Use: Type 4 / Type A wall tie for connecting two leaves of

a cavity wall. Suitable for 50-75mm cavities.

Notified Body: CERAM Research Limited

Queens Road, Penkhull STOKE-ON-TRENT ST4 7LQ

United Kingdom

Tel: +44 (0)1782 764444

Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity: 500N

Tensile Load Capacity: 1180N

Water Shedding Capability: Resistant

Durability: Material reference 23 / 3 (Steel grade 1.4482 /

1.4301)

Dangerous Substances: None

Conditions

Embedment Depth: min. 62.5mm

Minimum Mortar Class: Type M2 (iv)

Minimum Mortar Joint Width: 10mm

Recommended Spacing: Refer to Clause 6.2.2.2. PD 6697:2010

Authorised by:

2 James Q

Stuart Maxwell, Managing Director, on 16th May 2013

Manufactured by:

Ancon® BUILDING PRODUCTS

Ancon Building Products

President Way President Park Sheffield S4 7UR United Kingdom

Tel: +44 (0)114 275 5224 Fax: +44 (0)114 276 8543 Email: info@ancon.co.uk Web: www.ancon.co.uk Twitter: @AnconUK