

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018**Revision Date** 15-Nov-2018
Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name EVO-STIK FRAME SILICONE SEALANT BROWN
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word
None

Hazard statements
Not classified

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children

2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing
Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

PBT and vPvB assessment

This preparation contains substances considered to be persistent, bio-accumulating and toxic (PBT) or to be very persistent or very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	932-078-5	--	10 - <20	Asp. Tox. 1 (H304)		01-2119552497-29-xxxx
Silane, ethenyltrimethoxy-	220-449-8	2768-02-7	1 - <5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
Dodecamethylcyclhexa siloxane	208-762-8	540-97-6	0.1 - <1			01-2119517435-42-XXXX
Methyl alcohol	200-659-6	67-56-1	0.1 - <1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	01-2119392409-28-XXXX
Phosphoric acid	231-633-2	7664-38-2	0.1 - <1	Skin Corr. 1B (H314) Met. Corr. 1 (H290)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1B :: C>=25% Skin Irrit. 2 :: 10%<=C<25%	01-2119485924-24-xxxx

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical Name	CAS No.	SVHC candidates
Dodecamethylcyclhexasiloxane	540-97-6	X

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

Take a copy of the Safety Data Sheet when going for medical treatment.

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
-----------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of toxic and corrosive gases/vapours.
---	---

5.3. Advice for firefighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.
Other information	Ventilate the area. Prevent further leakage or spillage if safe to do so.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific Use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Chemical Name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Silane, ethenyltrimethoxy- (2768-02-7)

Type Worker Short term Systemic health effects
Exposure route Dermal
Derived No Effect Level (DNEL) 0.69 mg/kg bw/d

Type Worker Short term Systemic health effects
Exposure route Inhalation
Derived No Effect Level (DNEL) 4.9 mg/m³

Type Worker Long term Systemic health effects
Exposure route Dermal

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

Derived No Effect Level (DNEL) 0.69 mg/kg bw/d

Type Worker Long term Systemic health effects
Exposure route Inhalation
Derived No Effect Level (DNEL) 4.9 mg/m³

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Silane, ethenyltrimethoxy- (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid
Appearance Paste
Colour Brown
Odour No information available
Odour Threshold No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	301 °C	
Flash Point	100 °C	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour Pressure	No data available	
Vapour Density	No data available	
Relative Density	1.01	
Water Solubility	Immiscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition Temperature	>200 °C	
Decomposition Temperature	No data available	
Kinematic Viscosity	50 mm ² /s	
Dynamic Viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

9.2. Other information

Solid content (%)	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC (volatile organic compound)	No information available
Density	No information available
Bulk Density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	38,171.00 mg/kg
ATEmix (dermal)	8,820.00 mg/kg
ATEmix (inhalation-dust/mist)	191.24 mg/l
ATEmix (inhalation-vapour)	365.00 mg/l

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics --	LD50 > 5000 mg/kg (rat) OECD 401	LD50 > 2000 mg/kg (rabbit) OECD 402	
Silane, ethenyltrimethoxy- 2768-02-7	LD 50 = 7120 -7236 mg/kg (Rat) OECD 401	= 3360 µL/kg (Rabbit)	
Dodecamethylcyclhexasiloxane 540-97-6	> 50 g/kg (Rat)		
Methyl alcohol 67-56-1	= 2500 mg/kg (Rat)	200-1000 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h
Phosphoric acid 7664-38-2	= 1530 mg/kg (Rat)	= 2740 mg/kg (Rabbit)	> 850 mg/m ³ (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Hydrocarbons, C13-C23, n-alkanes, isoalkanes,	EL50 (72h) > 10 000 mg/L	LL50 (96h) > 1028 mg/L	-	LL50 (48h) > > 3193 mg/l (Acartia	-

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

cyclics, < 0.03% aromatics --	(Skeletonema costatum)	(Scophthalmus maximus)		tonsa)	
Silane, ethenyltrimethoxy- 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)	-
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-	-
Phosphoric acid 7664-38-2	-	LC50: 3 - 3.5mg/L (96h, Gambusia affinis)	-	EC50: =4.6mg/L (12h, Daphnia magna)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Dodecamethylcyclhexasiloxane 540-97-6	8.87	-
Methyl alcohol 67-56-1	-0.77	10

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This preparation contains substances considered to be persistent, bio-accumulating and toxic (PBT). or to be very persistent or very bioaccumulating (vPvB).

Chemical Name	PBT and vPvB assessment
Silane, ethenyltrimethoxy- 2768-02-7	The substance is not PBT / vPvB
Dodecamethylcyclhexasiloxane 540-97-6	PBT / vPvB substance
Methyl alcohol 67-56-1	The substance is not PBT / vPvB PBT assessment does not apply
Phosphoric acid 7664-38-2	The substance is not PBT / vPvB PBT assessment does not apply

12.6. Other adverse effects

Other Adverse Effects No information available.

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/ container to an approved landfill.
Contaminated packaging	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN Number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Marine Pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical Name	CAS No.
Dodecamethylcyclotrihexasiloxane	540-97-6

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No.	Restricted substance per REACH Annex XVII
Methyl alcohol	67-56-1	69.
Diocetyl tin oxide	870-08-6	

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical Name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H332 - Harmful if inhaled
H226 - Flammable liquid and vapour
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H370 - Causes damage to organs
H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL
Ceiling Maximum limit value *
PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

STEL (Short Term Exposure Limit)
Skin designation

Safety Data Sheet

EVO-STIK FRAME SILICONE SEALANT BROWN
Supersedes Date: 05-Nov-2018

Revision Date 15-Nov-2018
Revision Number 2

STOT RE Specific target organ toxicity - Repeated exposure
STOT SE Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 15-Nov-2018

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet