



## **DECLARATION OF PERFORMANCE**

### **No SNF\_DOP\_023**

1. Unique identification code of the product-type:

**Dow Corning Firestop 400**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: Printed on the packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Sealant intended for Non-structural Facade Interior applications EN15651-1**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Dow Corning Europe S.A.  
1 rue Jules Bordet, parc industriel zone C  
7180 Seneffe, Belgium**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The Notified Body performed Initial Type Testing according to EN 15651-1  
and reaction to fire system 3 and issued a test report**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not Applicable**



9. Declared performance

Essential Characteristic	Declared Performance	Test Standard	Harmonised Standard
Reaction to Fire	Class E	EN 13501-1 and the relevant test standards given therein	<b>EN 15651-1</b>
Release of Chemicals Dangerous to the Environment and Health	None	See product MSDS	
<b>Water Tightness and Air Tightness</b>			
Resistance to Flow	≤3mm	EN ISO 7390	
Loss of Volume	≤35%	EN ISO 10563	
Tensile properties at break	≥25%	EN ISO 8339	
Durability	Pass	EN ISO 8339 (without ageing) EN ISO 10591 (with ageing)	
<b>Conditioning: Method A</b> <b>Test Substrate: Mortar M1 (with Acrylic Primer Solution)</b>			

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Seneffe, 6 June 2014

Loriane Parisot  
 High Performance Building AETS manager EMEA