### SAFETY DATA SHEET

AC50 ACOUSTIC SEALANT AND ADHESIVE

Issued: 08/04/2003

Page 1

Revision No: 1

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** AC50 ACOUSTIC SEALANT AND ADHESIVE

Product code: AC50C4, 900

Use / description of product: No significant hazard.

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9 0SW

UNITED KINGDOM

Tel: +44 (0) 133 240 3456 Fax: +44 (0) 133 200 9418

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),

HYDRODESULPHURIZED HEAVY 1-10%

CAS: 64742-82-1 EINECS: 265-185-4

[-] R10; [N] R51/53; [Xn] R65

Contains: Contains a plasticised water based acrylic emulsion with dense fillers, very minor amounts of

white spirits (ca. 1%), dispersants, bocides, and acrylic associate thickeners.

## 3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

## 4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.Eye contact: Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

#### Issued: 08/04/2003

### SAFETY DATA SHEET

AC50 ACOUSTIC SEALANT AND ADHESIVE

Page 2

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

**Environmental precautions:** Do not discharge into drains or rivers.

**Clean-up procedures:** Wash the spillage site with large amounts of water.

### 7. HANDLING AND STORAGE

Storage conditions: Store in cool, well ventilated area. Store in original containers between +5 and +25°C. Storage

outside these paramaters will dramatically reduce shelf life and invalidates all product

warrenties.

Suitable packaging: Must only be kept in original packaging.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: White

Odour: Barely perceptible odour

**Evaporation rate:** Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Viscosity: Highly viscous

Viscosity value: 250-350

Viscosity test method: x 1000 cps - Brookfield HBDV2+, spindle S70, 10rpm @ 20`C

**Boiling point/range°C:** 100

Flammability limits %: lower: N/A

upper: N/A

Autoflammability°C: N/D

Vapour pressure: as water

**Relative density:** 1.68

**pH:** 8.5-9.9

## 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

Issued: 08/04/2003

## **SAFETY DATA SHEET**

AC50 ACOUSTIC SEALANT AND ADHESIVE

Page 3

### 11. TOXICOLOGICAL INFORMATION

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

# 12. ECOLOGICAL INFORMATION

Persistence and degradability: No data available. Bioaccumulative potential: No data available.

Other adverse effects: No data available.

### 13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

## 14. TRANSPORT INFORMATION

### ADR / RID

UN no: -

Shipping name: "NOT SUBJECT TO ADR"

## IMDG / IMO

UN no: -

# IATA / ICAO

UN no: -

## 15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

### 16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

R65: Harmful: may cause lung damage if swallowed.

# **SAFETY DATA SHEET**

## AC50 ACOUSTIC SEALANT AND ADHESIVE

Page 4

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.