

A/c 24 - 527670121 | 527670201 | 527670241 |
527670161

REVISION DATE: April 2007

1 / 5
SDS No.: 13033



SAFETY DATA SHEET IMPACT

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME IMPACT
 PRODUCT NO. 347502, 348103, 348301, 389106, 389113, 347908
 SUPPLIER BOSTIK LIMITED
 COMMON ROAD
 STAFFORD
 STAFFORDSHIRE ST16 3EH
 +44 1785 255141
 +44 1785 272650
 EMERGENCY TELEPHONE +44 1785 255141 +44 1785 272650

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANONE	201-159-0	78-93-3	10-30%	F;R11 Xi;R36 R66 R67
ETHYL ACETATE	205-500-4	141-78-6	10-30%	F;R11 Xi;R36 R66 R67
FORMALDEHYDE ...%	200-001-8	50-00-0	< 1%	Carc3;R40 T;R23/24/25 C;R34 R43
HEPTANE AND ISOMERS			5-10%	Xn;R65. Xi;R38. F;R11. N;R50/53. R67.
HEXANE, MIXTURE OF ISOMERS			1-5%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
METHYLCYCLOHEXANE	203-624-3	108-87-2	1-5%	F;R11 Xn;R65 Xi;R38 R67 N;R51/53
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, <0.1% BENZENE		64742-49-0	10-30%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
N-HEXANE	203-777-6	110-54-3	< 1%	F;R11 Repr3;R62 Xn;R65,R48/20 Xi;R38 R67 N;R51/53
PENTANE	203-692-4	109-66-0	< 1%	F+;R12 Xn;R65 R66 R67 N;R51/53
PROPAN-2-OL	200-661-7	67-63-0	< 1%	F;R11 Xi;R36 R67
ROSIN	232-475-7	8050-09-7	< 1%	R43

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Highly flammable. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. F;R11. N;R51/53. R67.

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

INGESTION

DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if irritation persists after washing.

IMPACT

EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam, carbon dioxide or dry powder.

SPECIFIC HAZARDS

Toxic gases/vapours/fumes of Carbon dioxide (CO₂). Carbon monoxide (CO).

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus. Avoid breathing vapour

ENVIRONMENTAL PRECAUTIONS

Prevent entry into drains and water courses.

SPILL CLEAN UP METHODS

Absorb onto sand, earth or absorbent granules. Pick up with non-sparking tools and place into metal containers with sealable lids. Mark containers with details of hazards and store in designated area ready for disposal.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Ground container and transfer equipment to eliminate static electric sparks. Store at moderate temperatures in dry, well ventilated area.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m ³	ST - ppm	ST - mg/m ³
BUTANONE	WEL	200 ppm(Sk)	600 mg/m ³ (Sk)	300 ppm(Sk)	899 mg/m ³ (Sk)
ETHYL ACETATE	WEL	200 ppm		400 ppm	
FORMALDEHYDE ...%	WEL	2 ppm	2.5 mg/m ³	2 ppm	2.5 mg/m ³
N-HEXANE	WEL	20 ppm	72 mg/m ³		
PROPAN-2-OL	WEL	400 ppm	999 mg/m ³	500 ppm	1250 mg/m ³

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Explosion-proof general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level. Wear mask supplied with: Gas cartridge suitable for organic substances.

IMPACT

HAND PROTECTION

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Yellowish
ODOUR	of solvents
SOLUBILITY	Insoluble in water
RELATIVE DENSITY	0.84

10 STABILITY AND REACTIVITY

STABILITY

Avoid: Heat, sparks, flames.

11 TOXICOLOGICAL INFORMATION

INHALATION

Drowsiness, dizziness, disorientation, vertigo.

SKIN CONTACT

Prolonged contact may cause dryness of the skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment. Contamination of the terrestrial and aquatic environments should be avoided.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste is classified as hazardous waste.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS

3

PROPER SHIPPING NAME

ADHESIVES

IMPACT

UN NO. ROAD	1133	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	3Y
CEPIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1133
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E, S-D	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1133
AIR CLASS	3	AIR PACK GR.	III

15 REGULATORY INFORMATION

LABELLING



Irritant



Highly Flammable



Dangerous for the environment

RISK PHRASES

R11	Highly flammable.
R36/38	Irritating to eyes and skin.
R51/53	Toxic to aquatic organisms. may cause long-term adverse effects in the aquatic environment
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S29/50	Do not empty into drains. dispose of this material and its container at hazardous or special waste collection point.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P14	Contains ROSIN. May produce an allergic reaction.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108). Introduction to Local Exhaust Ventilation HS(G)37.

16 OTHER INFORMATION

GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

REVISION DATE: April 2007

SDS No.: 13033

IMPACT

REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Boelik Limited.

ISSUED BY

Approved ID

REVISION DATE April 2007

REV. NO./REPL. SDS GENERATED 3

DATE August 2006

RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.