



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: SKFLEXEBT/1-CPR/ 2013

Substrate: Mortar M1

Primer: Sika Primer-3 N

1. Identification Code	Sikaflex EBT+ (colours); Codes: SKFLEXEBTBG/BK/BN/GY/WE
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
4. Manufacturer	Sika Factory reference 02 05 06 01 150 00000 08
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-1 (2012)
Type	F EXT-INT
Classification	F12.5E
Reaction to Fire	Class F
Loss of Volume ISO10563	≤25%



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Durability ISO 8340, ISO 9047 and ISO 10590	Pass

Substrate: Mortar M1

Primer: Sika Primer-3 N

1. Identification Code	Sikaflex EBT+ (colours); Codes: SKFLEXEBTBG/BK/BN/GY/WE
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 4: Sealants for Pedestrian Walkways
4. Manufacturer	Sika Factory reference 02 05 06 01 150 00000 08
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-4 (2012)
Type	PW-EXT-INT
Classification	PW12.5E
Reaction to Fire	Class F



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

Loss of Volume ISO10563	≤15%
Resistance to flow ISO7390	≤5 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Tear Resistance EN15651-4, 4.3.2.7	Crack width ≤12mm
Elastic recovery ISO 7389	≥40%
Durability ISO 8340, ISO 9047 and ISO 10590	Pass
Outdoor requirement; Adhesion and cohesion properties after exposure to artificial irradiation ISO11431	NF
Outdoor requirement; Adhesion and cohesion properties at maintained extension after immersion in water for 28 days (EN15651-4)	NF
Outdoor requirement; Adhesion and cohesion properties at maintained extension after immersion in salt water for 28 days (EN15651-4)	NF

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 24/2/14