



CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: SKFLEXEBTCR /2-CPR/ 2014

Substrate: Anodized Aluminium

Primer: No primer used

1. Identification Code	SIKAFLEX EBT+ CLEAR Codes: SKFLEXEBTCR
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
4. Manufacturer	Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-1 (2012)



Type	F EXT-INT-CC
Classification	F20LM
Reaction to Fire	Class E
Loss of Volume ISO10563	≤10%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties (-30°C)	NF
Durability	Pass

Substrate: Anodized Aluminium

Primer: No primer used

1. Identification Code	SIKAFLEX EBT+ CLEAR Codes: SKFLEXEBTCR
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements
4. Manufacturer	Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable



9. Declared Performance		TO EN15651-3 (2012)
Type	S	
Classification	XS2	
Reaction to Fire	Class E	
Loss of Volume ISO10563	≤20%	
Resistance to flow ISO7390	≤3 mm	
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF	
Action of the microorganisms : Intensity of growth ISO 846, method B	1	
Durability	Pass	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 23/6/14