



# SAFETY DATA SHEET WOOD ADHESIVE INTERIOR

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME

WOOD ADHESIVE INTERIOR

PRODUCT NO.

715811, 715835, 715997, 715110, 715189, 715219, 715301, 715417, 715678, 715615, 715813, 715912,

716048, 716022, 716049

SUPPLIER

BÓSTIK LIMITED COMMON ROAD

STAFFORD

STAFFORDSHIRE ST18 3EH

+44 1785 255141 +44 1785 272650

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
N-BLITYL ESTER OF GLYCOLLIC ACID		7397-82-8	1-5%	Xi;R41.

The Full Text for all R-Phrases are Displayed in Section 16

## 3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

## 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT induce vorniting. Get medical attention immediately.

## SKIN CONTACT

Remove affected person from source of contamination. Rinse the skin immediately with lots of water. Get medical attention if imitation persists after washing.

## EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for et least 15 minutes and get medical attention.

## 5 FIRE-FIGHTING MEASURES

## EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

## SPECIFIC HAZARDS

Fire or high temperatures create: Toxic gases/vapours/furnes of Cerbon dioxide (CO2). Carbon monoxide (CO).

## PROTECTIVE MEASURES IN FIRE

Wear self contained breathing apparatus

# 6 ACCIDENTAL RELEASE MEASURES

# SPILL CLEAN UP METHODS

Stop leak if possible without risk. Do not contaminate water sources or sewer. Pick up with vacuum or absorbent solid, store in closed container for disposal. Avoid generation and spreading of dust. Avoid contact with skin or inhaletion of spillage, dust or vapour. Wear necessary protective equipment. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

## 7 HANDLING AND STORAGE

2 / 3

REVISION DATE: April 2006

## **WOOD ADHESIVE INTERIOR**

SOS No.: 12702

## **USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Do not handle broken packages without protective equipment. Use mechanical ventilation in case of handling which causes formation of dust.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





#### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

#### **ENGINEERING MEASURES**

All handling to take place in well-ventileted area.

#### RESPIRATORY EQUIPMENT

Wear respirator if there is dust formation.

## HAND PROTECTION

Use suitable protective gloves if risk of skin contact. Use thin cotton gloves inside the rubber gloves if ellergy risk.

#### EYE PROTECTION

If risk of apleahing, wear safety goggles or face shield.

#### OTHER PROTECTION

Weer suitable protective clothing as protection against splashing or contamination.

#### HYGIENE MEASURES

Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, emoking and using the toilet. Use appropriate skin cream to prevent drying of skin. DO NOT SMOKE IN WORK AREA!

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

ونتونا

COLOUR

White

SOLUBILITY

Miscible with water.

RELATIVE DENSITY

1.1 @ 25 °c

## 10 STABILITY AND REACTIVITY

## STABILITY

Stable under normal temperature conditions.

## CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

## MATERIALS TO AVOID

No incompatible groups noted.

# HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

## 11 TOXICOLOGICAL INFORMATION

## **HEALTH WARNINGS**

Dust may irritate respiratory system. Serious long-term effects are not known to be related to this type of product.

Particles in the eyes may cause irritation and smarting. May cause discomfort if swallowed.

3 / 3

REVISION DATE: April 2006

**WOOD ADHESIVE INTERIOR** 

SDS No.: 12702

12 ECOLOGICAL INFORMATION

**ECOTOXICITY** 

Not regarded as dangerous for the environment. However, contamination of the equatic or terrestrial environments should be avoided

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and recieim or recycle, if practical.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA,

ADR/RID).

No transport warning sign required.

ADRILABEL NO.

0

MARINE POLLUTANT

No.

15 REGULATORY INFORMATION

RISK PHRASES

NC

Not classified.

SAFETY PHRASES

S2

Keep out of the reach of children

\$36/37/39

Wear suitable protective clothing, gloves and eye/face protection.

P13

Safety data sheet available for professional user on request.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

# 16 OTHER INFORMATION

## GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

## INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

## REVISION COMMENTS

This sefety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

ISSUED BY

Approved EC

REVISION DATE

April 2008

REV. NO TREPL. SOS GENERATED 5

DATE

Feb 2003

RISK PHRASES IN FULL

R41

Risk of serious damage to eyes.