

SAFETY DATA SHEET DUNLOP CX-24 ESSENTIAL TILE ADHESIVE GREY

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name DUNLOP CX-24 ESSENTIAL TILE ADHESIVE GREY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cement based adhesive.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent ST4 8JB 01782 591100

Contact person sdsreply@building-adhesives.com

1.4. Emergency telephone number

Emergency telephone 01865 407 333 (24hr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Human health When the cement based powder is mixed with water or admixture, a strongly alkaline paste is

produced. Cement based products may, until set, cause both irritant and allergic contact dermatitis. Irritrant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts. Corrosive. Prolonged contact

causes serious eye and tissue damage.

Environmental The product is not expected to be hazardous to the environment.

2.2. Label elements

Hazard pictograms





Signal word Danger

Revision date: 21/01/2020

DUNLOP CX-24 ESSENTIAL TILE ADHESIVE GREY

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with local regulations.

Contains ORDINARY PORTLAND CEMENT

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ORDINARY PORTLAND CEMENT

30-60%

CAS number: 65997-15-1 EC number: 266-043-4

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

CALCIUM FORMATE <1%

CAS number: 544-17-2 EC number: 208-863-7

Classification

Eye Dam. 1 - H318

The full text for all hazard statements is displayed in Section 16.

Composition comments This product contains a reducing agent to ensure that the CrVI content of the cement in the

product remains below 2ppm during the defined shelf life of the product.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention immediately.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact Remove affected person from source of contamination. Do not rub eye. Remove any contact

lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical

attention immediately. Continue to rinse.

Revision date: 21/01/2020

DUNLOP CX-24 ESSENTIAL TILE ADHESIVE GREY

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases.

Ingestion May cause chemical burns in mouth and throat.

Skin contact May cause serious chemical burns to the skin.

Eye contact May cause severe eye irritation. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m3. Oxides of carbon. Oxides of nitrogen. No unusual fire or explosion hazards noted.

Hazardous combustion

products

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known. Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid contact with skin or inhalation of spillage, dust or vapour. Dampen spillage with water.

Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty

of water.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11

for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid handling

which leads to dust formation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in

the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ORDINARY PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

CALCIUM FORMATE (CAS: 544-17-2)

DNEL Workers - Dermal; Short term systemic effects: 4780 mg/kg/day

Workers - Inhalation; : 337 mg/m3

Workers - Dermal; Short term local effects: 16.7 mg/cm²

General population - Dermal; Short term systemic effects: 2390 mg/kg/day

General population - Inhalation; : 83.2 mg/m³

General population - Dermal; Short term local effects: 8.3 mg/cm²

General population - Oral; : 23.9 mg/kg/day

8.2. Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166

should comply with European Standard EN166.

Hand protection

Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. The selected gloves should have a breakthrough time of at least >8 hours. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Use respiratory

equipment with particle filter type P2

Thermal hazards Not applicable.

Environmental exposure

controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Dusty powder.

Colour Grey.

Odour Odourless.

pH pH (concentrated solution): pH12-13 after mixing

Melting point Not applicable.

Initial boiling point and range Not applicable.

Solubility(ies) Slightly soluble in water.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not determined.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid contact with acids. Water, moisture.

10.5. Incompatible materials

Materials to avoid Acids - oxidising.

10.6. Hazardous decomposition products

Hazardous decomposition

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (dusts/mists 100.0

mg/l)

Skin corrosion/irritation

Skin corrosion/irritation Severe skin irritation.

Extreme pH ≥ 11.5

Serious eye damage/irritation

Serious eye damage/irritation Severely irritating to skin. Irritation of eyes is assumed. No testing is needed.

Revision date: 21/01/2020

DUNLOP CX-24 ESSENTIAL TILE ADHESIVE GREY

Respiratory sensitisation

Respiratory sensitisation Not known.

Skin sensitisation

Skin sensitisation May cause sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro

Based on available data the classification criteria are not met.

Genotoxicity - in vivo

Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not relevant.

Inhalation May cause respiratory system irritation. May cause damage to mucous membranes in nose,

throat, lungs and bronchial system. Harmful: danger of serious damage to health by prolonged

exposure through inhalation.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal

tract.

Skin contact The product contains a small amount of sensitising substance. May cause sensitisation or

allergic reactions in sensitive individuals.

Eye contact Risk of serious damage to eyes. May cause chemical eye burns.

Acute and chronic health

hazards

Repeated exposure in excess of the WEL has been linked with rhinitis and coughing. Skin

exposure has been linked to allergic chromium dermatitis.

SECTION 12: Ecological information

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic

organisms.

12.1. Toxicity

ToxicityThe product is not expected to be hazardous to the environment (LC50 aquatic toxicity rating

not determined). The addition of cement based product to water will, however, cause the pH

to rise and may, therefore, be toxic to aquatic life in some circumstances.

12.2. Persistence and degradability

Persistence and degradability Not relevant. After hardening, cement presents no toxicity risks.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will sediment in water

systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Product that has exceeded defined shelf life should be treated with a reducing agent or

disposed of according to the National or Devolved Administration legislation. For small spillages, isolate spillage then harden with water before disposing in accordance with National

or Devloved Administration legislation.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

Road transport notes Not classified.

Rail transport notes Not classified.

Sea transport notes Not classified.

Air transport notes Not classified.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as

amended).

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments 1

Issued by Technical Manager

Revision date 21/01/2020

SDS number 20559

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.