

Construction Products Regulations (EU) 305 2011

1 Identification Code: 2. Batch Identification:	Bond-It Pro-mate Glazing Silicone By batch number – see print on packaging	
3. Intended uses:	F EXT-INT Façade Sealant for Exterior and Interior 12.5E. G 20LM Glazing Sealant	
4. Manufacturer:	Seal It Services t/a Bond It Unit G16 River Bank Way Lowfields Business Park Elland West Yorkshire HX5 9DN	
5. Authorised Representative:	Not applicable	
6. System of assessment and Verification of constancy:	System 3	
7. Notified Body:	0074	
8. European Technical Assessment:	Not Applicable	

DECLARATION OF PERFORMANCE DOP BDPM

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤30%	Tested on aluminium with
Tensile properties after water	NF	primer
immersion		
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

PRodend

Phil Radford Technical Manager Elland 26 June 2014