SAFETY DATA SHEET

Date of issue/Date of revision

: 29 November 2016 Version : 1.01



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: LEYLAND TRADE Truguard Path & Patio Seal
Product code	: 17001DUT066
Other means of identification	: Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against	st
---	----

Product use	Consumer applications, Professional applications, Used I	by spraying.
Use of the substance/ mixture	Coating.	

1.3 Details of the supplier of the safety data sheet

PPG Architectural Coatings UK Ltd Huddersfield Road Birstall, West Yorkshire WF179XA United Kingdom +44 (0) 1924 354000 Fax: +44 (0) 1924 354533

e-mail address of person	: regulatoryaffairs@ppg.com
responsible for this SDS	

1.4 Emergency telephone number

Supplier

Telephone number : +44 (0) 1924 354000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830) -
United Kingdom (UK)	

Code: 17001DUT066Date of issue/Date of revision: 29 November 2016LEYLAND TRADE Truguard Path & Patio Seal

SECTION 2: Hazards identification

Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Not applicable.	
	P102, P101	
Hazardous ingredients	Not applicable.	
Supplemental label elements	Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.	
Special packaging requirements		
Containers to be fitted with child-resistant fastenings	Not applicable.	
Tactile warning of danger	Not applicable.	

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

			Classification	
Product/ingredient name	Identifiers	% by weight	Regulation (EC) No. 1272/2008 [CLP]	Туре
2-methylpropan-2-ol Siloxanes and Silicones, di-Me, [[[3-[(2-aminoethyl)amino]propyl] dimethoxysilyl]oxy]-terminated	REACH #: 01-2119444321-51 EC: 200-889-7 CAS: 75-65-0 Index: 603-005-00-1 CAS: 71750-80-6	≥1.0 - ≤5.0 ≥1.0 - ≤4.9	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Code : 17001DUT066

Date of issue/Date of revision

: 29 November 2016

LEYLAND TRADE Truguard Path & Patio Seal

SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures : Remove contact lenses, irrigate copiously with clean, fresh water, holding the evelids Eye contact apart for at least 10 minutes and seek immediate medical advice. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Skin contact Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. **Over-exposure signs/symptoms** Eye contact : No specific data. Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data. 4.3 Indication of any immediate medical attention and special treatment needed Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. Specific treatments : No specific treatment. SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Llemende from the	In a fire or if heated, a pressure increase will essure and the container may burst

Hazards from the	1	In a fire or if heated, a pressure increase will occur and the container may burst.	
substance or mixture			

United Kingdom (UK)		
Code : 17001DUT060		
SECTION 5: Firefigh	iting measures	
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides Formaldehyde.	
5.3 Advice for firefighters		
Special precautions for fire fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. 	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for c	cor	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Storage temperature: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

solutions

Occupational exposure limits

Product/ingredient name		Exposure limit values	
2-methylpropan-2-ol		EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 462 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 308 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.	
procedures	atmosphere or of the ventilation protective equip the following: E the assessmen limit values and atmospheres - exposure to che (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectivene n or other control measures and/or the necessity to use respirator oment. Reference should be made to monitoring standards, such European Standard EN 689 (Workplace atmospheres - Guidance t of exposure by inhalation to chemical agents for comparison with I measurement strategy) European Standard EN 14042 (Workpla Guide for the application and use of procedures for the assessme emical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedure ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also b	y for n ace ent of ures
English (GB)		United Kingdom (UK)	5/12

Code : 17001DUT066 LEYLAND TRADE Truguard F		Date of issue/Date of revision: 29 November 2016& Patio Seal
SECTION 8: Exposur	re c	ontrols/personal protection
		required.
DNELs - Not available.		
PNECs PNECs - Not available.		
8.2 Exposure controls		
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measu	<u>ures</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, befor eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety glasses with side shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	:	nitrile rubber, butyl rubber, PVC, Viton®
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection		Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipmer will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physic	al ar	id chemical properties
<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	White.
Odour	:	Faint odour.
Odour threshold	:	Not available.
рН	:	8.5
Melting point/freezing point	:	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No.	2015/830 -
United Kingdom (UK)	

Code : 17001DUT066	Date of issue/Date of revision	: 29 November 2016		
LEYLAND TRADE Truguard Path & Patio Seal				
SECTION 9: Physical and chemical properties				

		• •
		May start to solidify at the following temperature: 25°C (77°F) This is based on data for the following ingredient: 2-methylpropan-2-ol. Weighted average: -0. 52°C (31.1°F)
Initial boiling point and boiling range	:	>37.78°C
Flash point	:	Closed cup: Not applicable. [Product does not sustain combustion.]
Evaporation rate Material supports combustion. Flammability (solid, gas) Upper/lower flammability or		95 (2-methylpropan-2-ol) compared with butyl acetate No. liquid Not applicable.
explosive limits		
Vapour pressure	÷	Highest known value: 5.4 kPa (40.6 mm Hg) (at 20°C) (2-methylpropan-2-ol). Weighted average: 3.18 kPa (23.85 mm Hg) (at 20°C)
Vapour density	1	Highest known value: 2.6 (Air = 1) (2-methylpropan-2-ol).
Relative density	÷	1
Solubility(ies)	1	Partially soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	1	Not applicable.
Auto-ignition temperature	1	Not applicable.
Decomposition temperature	÷	Stable under recommended storage and handling conditions (see Section 7).
Viscosity	÷	Kinematic (40°C): >0.21 cm²/s
Explosive properties	÷	Product does not present an explosion hazard.
Oxidising properties	ł	Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	:	The product is stable.		
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.		
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.		
10.6 Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds Formaldehyde. metal oxide/ oxides		

Code : 17001DUT066

LEYLAND TRADE Truguard Path & Patio Seal

Date of issue/Date of revision

: 29 November 2016

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-methylpropan-2-ol	LC50 Inhalation Gas.	Rat	14100 ppm	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	2733 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

	Route	ATE value	
Inhalation (gases)		1030701.8 ppm	
Irritation/Corrosion			
Conclusion/Summary	: Not available.		
Sensitisation			
Conclusion/Summary	: Not available.		
<u>Mutagenicity</u>			
Conclusion/Summary	: Not available.		
Carcinogenicity			
Conclusion/Summary	: Not available.		
Reproductive toxicity			
Conclusion/Summary	: Not available.		
Teratogenicity			
Conclusion/Summary	: Not available.		

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-methylpropan-2-ol	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure	: Not available.				
Potential acute health ef	fects				
Inhalation	: No known significant effects or critical hazards.				
Ingestion	: No known significant effects or critical hazards.				
Skin contact	: No known significant effects or critical hazards.				
Eye contact	: No known significant effects or critical hazards.				
Symptoms related to the	Symptoms related to the physical, chemical and toxicological characteristics				
Inhalation	: No specific data.				
Ingestion	: No specific data.				
Skin contact	: No specific data.				
Eye contact	: No specific data.				

Code: 17001DUT066Date of issue/Date of revision: 29 November 2016LEYLAND TRADE Truguard Path & Patio Seal

SECTION 11: Toxicological information

Delayed and immediate effe	cts	as well as chronic effects from short and long-term exposure		
<u>Short term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	1	Not available.		
<u>Long term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Potential chronic health effe	cts	<u>5</u>		
Not available.				
Conclusion/Summary	:	Not available.		
General	1	No known significant effects or critical hazards.		
Carcinogenicity	4	No known significant effects or critical hazards.		
Mutagenicity	1	No known significant effects or critical hazards.		
Teratogenicity	1	No known significant effects or critical hazards.		
Developmental effects	1	No known significant effects or critical hazards.		
Fertility effects	4	No known significant effects or critical hazards.		
Other information	1	Not available.		

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

- 12.2 Persistence and degradability
- **Conclusion/Summary** : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-methylpropan-2-ol	0.35	5.01	low

12.4 Mobility in soil

English (GB)

Code : 17001DUT066 LEYLAND TRADE Truguard Path & Patio Seal	Date of issue/Date of revision	: 29 November 2016		
SECTION 12: Ecological information				

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment				
PBT	: Not applicable.			
vPvB	: Not applicable.			

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as

European waste catalogue (EWC)

	Waste code	Waste designation
	08 01 12	waste paint and varnish other than those mentioned in 08 01 11
P	ackaging	

Methods	ot	disposa	L

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging		European waste catalogue (EWC)
Container	15 01 02	plastic packaging
Special precautions	 This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. 	

14. Transport information

-				
	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
English (GB)		United Kingdom	 (UK)	10/12

Code : 17001DUT066 LEYLAND TRADE Truguard Path & Patio Seal	Date of issue/Date of revision	: 29 November 2016
14. Transport information		

14.5 Environmental	No.	No.	No.	No.
hazards				
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
ADN	: None identified.
IMDG	: None identified.
IATA	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Other EU regulations

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Code : 17001DUT066 LEYLAND TRADE Truguard Path & Patio Seal		Date of issue/Date of revision : 29 November 2016				
SECTION 16: Other information						
Classification			Justification			
Not classified.						
Full text of abbreviated H s	statements					
H225 H315 H319 H332 H335		Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.				
Full text of classifications	[CLP/GHS]					
Eye Irrit. 2, H319 Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H335		ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3				
<u>History</u> Date of issue/ Date of revision	: 29 November 2	016				
Date of previous issue	: 24 August 2016	5				
Prepared by	: EHS					
Version	: 1.01					

In einformation contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.