

Revision No. 002 Issue Date: July 2012

Material Safety Data Sheet

1. Identification of the Substance / Preparation and Company

Product Name: Artex Heritage Plaster Cove

Artex Heritage Ceiling Roses

Artex 100, 127 & 135 (paper) Faced Cove

Artex Sculptured Cove

Description: Paper faced and plaster mouldings

Supplier Details: Artex Limited

Pasture Lane Ruddington Nottingham NG11 6AE

Telephone (UK): 0800 032 6345

Telephone (Non-UK): +44 (0) 115 984 5679

Facsimile: 0800 917 7632

Email: artextechnical@saint-gobain.com

2. Hazards Identification

Non-hazardous

Keep dry. Do not breathe dust when cutting and avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

3. Composition / Information on Ingredients/

Calcium sulphate	< 95%
Paperboard	< 10%
Glass rovings	< 5%
Impurities (silica)	< 1%

4. First Aid Measures

Inhalation: Where dust is inhaled, remove to fresh air, ensuring the patient's air passages are clear.

Eye contact: Material in the eye should be rinsed out using an eye wash bottle or copious quantities of clean water. Seek medical advice

Please note should any symptoms persist obtain medical assistance.

5. Fire Fighting Measures

The products are fire resistant, but packaging may burn.

Use suitable extinguishing media – water, foam, carbon dioxide or dry powder, observing normal fire fighting procedures.

6. Accidental Release Measures

Personal Precaution Measures

Control and suppress dust formation, while cutting.

Environmental Precaution Measures

These materials contain high levels of sulphate, and are subject to national regulatory control for disposal.

Refer to section 8 – Exposure Controls/Personal Protection

Refer to section 13 - Disposal Considerations

7. Handling and Storage

Use

Minimise and control dust formation while cutting.

Refer to section 2 – Hazard Identification

Refer to section 8 – Exposure Controls/Personal Protection

Manual Handling

Careful handling and smooth transportation will reduce the risk of damage to the product and ensure best results. Always carry plaster cove on its edge and ensure it is well supported along its entire length. Use on-package handles where available to ensure damage is minimised.

Use correct manual handling techniques.

Mechanical Handling

In order to maintain the stability of the palletised load, it is important that the lift truck fork length and centres are set to correctly support the load.

Storage

Store in dry conditions, in original packaging. Rotate stocks, and avoid damaging the packaging.

To maintain stability, place pallets on firm level ground. Do not stack more than one lift high.

8. Exposure Controls and Personal Protection / /

Occupational Exposure Standards (OES) for bulk ingredients:

Substance	Total Inhalable (8 hour TWA)	Respirable (8 hour TWA)
Calcium Sulphate	10mg.m ⁻³ OES	4mg.m ⁻³ OES

TWA – time weighted average

Exposure Controls - Occupational

Respiratory Protection: Control dust formation and ventilate the working area.

Hand Protection: To avoid prolonged or repeated contact wear impermeable gloves. Certain individuals may be skin sensitive. To reduce the effect of hand contact, apply a barrier cream.

Body Protection: Avoid unnecessary skin contact.





Material Safety Data Sheet

9. Physical and Chemical Properties

Appearance

White or off-white solid moulding

Odour

Odourless

pН

6-8

10. Stability and Reactivity

Under normal conditions of use, these products are stable and unreactive.

Conditions to Avoid

Stable but should be kept away from fire.

Materials to Avoid

None.

Hazardous Decomposition Products

None, under normal conditions of use.

11. Toxicological Information

Non-toxic.

12. Ecological Information

Keep contained and away from waterways

13. Disposal Considerations

Packaging Disposal

Dispose of empty packaging in accordance with local Environmental Agency Regulations.

Product Disposal

Dispose of product in accordance with local Environmental Agency Regulations. These products have specific disposal requirements because of the high sulphate content.

14. Transport Information

No special precautions exist with respect to transport.

Not classified as hazardous for transport.

Keep packaging dry and undamaged. This product is fragile, ensure it is well supported along its entire length during transportation.

15. Regulatory Information

Note sulphate waste regulations.

Safety Data Sheet prepared in accordance with:

Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 – CHIP 3.

Approved Code of Practice (L130), "The Compilation of Safety Data Sheets" (3rd edition).

The Control of Substances Hazardous to Health 1999 (COSHH).

COSHH Essentials: Easy Steps to Control Chemicals.

16. Other Information

Sources of key data used to compile Safety Data Sheet:

Approved Classification and Labelling Guide – Guidance on Regulations L131

Approved Supply List (L129) (7th edition)

HSE EH40 Occupational Exposure Limits (current edition)

This information reflects typical values and is not a product specification.

No warranty is hereby expressed or implied.

Note to User:

This safety data sheet does not constitute the users own workplace risk assessment, which is required under COSHH Regulations 1999.

 $Artex, Thistle, Blue \ Hawk, Gyproc, Speed Tape, Speed Tape \ PRO \ and \ Gypframe \ are \ all \ registered \ trademarks \ of \ BPB \ United \ Kingdom \ Limited \ part \ of \ the \ Saint-Gobain \ Group, \ Gro$

Artex Limited reserve the right to revise any product specification without notice. The information given is correct to the best of our knowledge at the time of publication, but it is the user's responsibility to ensure it remains current prior to use. The enclosed information should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products, systems and specification being used and their subsequent installation prior to the commencement of work or a job.

We advise that you read and familiarise yourself with all the information contained in this literature prior to the commencement of the work, job or specification. For a comprehensive and up to date library of information visit our website at: www.artexltd.com

Telephone: 0800 032 6345 Fax: 0800 917 7632 E-mail: artextechnical@saint-gobain.com Product Training Centre: 0844 561 8810



