



## **Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

## CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

## No JETMIX/1-CPR/2013

| 1. Identification Code                                     | Jetcem Premix Sand and Cement   |
|--|---|
|  | Codes: JETMIX2, JETMIX6   |
| 2. Type, Batch and/or Serial Number                        | For batch number see packaging  |
| 3. Intended use  | Concrete repair product for structural and non structural repair. CC Mortar (based on hydraulic cement) |
|  | EN1504-3 Principle 3.1  |
| 4. Manufacturer  | Everbuild Building Products Itd, Site 41, Cross Green   |
|  | Industrial Estate, Knowsthorpe Way, Leeds, LS90SW, UK.  |
| 5. Authorised Representative                               | Not Applicable  |
| 6. Assessment and Verification of Constancy of Performance | System 2+   |
| 7. Notified Body and Tasks                                 | BSI (0086) Initial inspection and ongoing surveillance of F.P.C. system                                 |
|  | Certificate of conformity reference 0086-CPD- 597711  |
| 8. European technical Assessment                           | Not applicable  |
|  |   |
|  |   |
|  |   |



## **Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

|                                    | website: www.everbuild.co.uk                             |
|------------------------------------|--|
| 9. Declared Performance            | EN1504-3 (2005) ) Concrete repair product for structural |
|                                    | repair. CC mortar (based on hydraulic cement) Class R3   |
| Compressive Strength               | Class R3   |
| Chloride ion content               | <u>&lt;</u> 0.05%  |
| Adhesion strength by pull off test | >1.5MPa  |
| Restrained shrinkage/expansion     | NPD  |
| Carbonation resistance             | NPD  |
| Elastic Modulus                    | <u>&gt;</u> 15GPa  |
| Thermal Compatibility: Part 4 Dry  | ≥ 1.5MPa   |
| Cycling                            |  |
| Skid resistance                    | NPD  |
| Coefficient of thermal expansion   | NPD  |
| Capillary Adsorption               | NPD  |
| Dangerous substances               | Complies with 5.4  |
| Reaction to Fire                   | Class A1   |
|                                    |  |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/201