



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No JETCEM/1-CPR/2013

| | |
|--|---|
| 1. Identification Code | Jetcem Rapid Set Cement Codes: JETCEM2, JETCEM3, JETCEM6 |
| 2. Type, Batch and/or Serial Number | For batch number see packaging |
| 3. Intended use | Concrete repair product for non- structural repair. CC Mortar (based on hydraulic cement) EN1504-3 Principle 3.1 |
| 4. Manufacturer | Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS90SW, UK. |
| 5. Authorised Representative | Not Applicable |
| 6. Assessment and Verification of Constancy of Performance | System 2+ |
| 7. Notified Body and Tasks | BSI (0086) Initial inspection and ongoing surveillance of F.P.C. system Certificate of conformity reference 0086-CPD- 597711 |
| 8. European technical Assessment | Not applicable |
| | |
| | |



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

| | |
|---|--|
| 9. Declared Performance | EN1504-3 (2005)) Concrete repair product for non structural repair. CC mortar (based on hydraulic cement) Class R2 |
| Compressive Strength | Class R4 |
| Chloride ion content | ≤ 0.05% |
| Adhesion strength by pull off test | ≥ 1.5MPa |
| Restrained shrinkage/expansion | NPD |
| Carbonation resistance | NPD |
| Elastic Modulus | ≥ 15GPa |
| Thermal Compatibility: Part 4 Dry Cycling | ≥ 0.8MPa |
| Skid resistance | NPD |
| Coefficient of thermal expansion | NPD |
| Capillary Adsorption | ≤0.5kg/m²h^{0.5} |
| Dangerous substances | Complies with 5.4 |
| Reaction to Fire | Class A1 |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/201