

DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

No. DoP-GB- weberpral M -13082019

1. *Unique identification code of the product-type:*
Weberpral M
2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*
Weberpral M (batch/production date/ production site is printed on packaging).
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Factory-made designed render for use on external wall as a One Coat render (OC class)
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):*
Saint-Gobain Construction Products UK Ltd. trading as Saint-Gobain Weber
Dickens House
Enterprise Way
Flitwick
Beds
MK45 5BY
UK

Web: www.uk.weber
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
Not applicable
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
AVCP system 4
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
EN 998-1:2016
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
Not applicable


9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Dry bulk density	1200 – 1600 kg/m ³	BS EN 1015-10:1999 (EN 998-1:2016)
Compressive strength	NPD	BS EN 1015-11:1999 (EN 998-1:2016)
Capillary water absorption	W _c 2 class	BS EN 1015-18:2002 (EN 998-1:2016)
Water vapour permeability	μ < 35	BS EN 1015-19:1999 (EN 998-1:2016)
Thermal conductivity	0.61 W/(m.K)	EN 1745:2012, Table A.12 (EN 998-1:2016)
Reaction to fire	A1	BS EN 998-1:2016, 5.3.3
Durability:		EN 998-1:2016, 5.3.2
Adhesion after weathering cycles	≥ 0.2 N/mm ² – FP: A, B, C	BS EN 1015-21:2002 (EN 998-1:2016)
Water permeability after weathering cycles	≤ 1ml/cm ²	
Dangerous substances	See MSDS	EN 998-1:2016, 5.3.4

NPD = No performance determined

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:
Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:


 (signature)

(name and function)

(place and date of issue)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

- (31) Safety data sheet: MSDS (weberpral M)
- (33) Information on substances of very high concern: Not applicable