



BS EN 934-2

07

0086

## DECLARATION OF PERFORMANCE

**Sika® 1+**

02	07	05	04	001	0	000001	1088
----	----	----	----	-----	---	--------	------

<b>1. Product Type:</b> Unique identification code of the product-type:	<b>Sika® 1+</b>
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	<b>1+</b> (Batch No See packaging)
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	<b>Water resisting concrete admixture according to BS EN 934-2 (Table 9)</b>
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	<b>Sika® 1+</b>  <b>Sika Limited</b> <b>Watchmead</b> <b>Welwyn Garden City</b> <b>Hertfordshire</b> <b>AL7 1BQ</b> <b>United Kingdom</b>
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	<b>Not Relevant (see 4)</b>
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	<b>System 2+</b>
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	<b>0086</b>  <b>Notified factory production control certification body No. 0086 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 472347</b>

Declaration of Performance



<p><b>8. Notified body (ETA):</b>          In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:</p>	<p><b>Not relevant (see 7)</b></p>
---	------------------------------------

**9. Declared performance**

Essential Characteristics	Performance	Harmonised technical specification
Chloride ion content	Max 0.1% by wt	EN 934-2:2009 +A1:2012
Alkali content	Max 0.10% by wt	
Capillary absorption	Tested for 7 days after 7 days curing: test mix ≤ 50% by mass of control mix Tested for 28 days after 90 days curing: test mix ≤ 60% by mass of control mix	
Compressive strength	At 28 days: test mix ≥85% of control mix	
Air content	Test mix ≤ 2% by volume above control mix	
Corrosion behaviour	Contains only substances according to EN 934-1 Annex A.1	
Dangerous substances	NPD	



Concrete  
Declaration of Performance  
Edition 02.2013  
Identification no. 02 07 05 04 001 0 000001  
Version no. 01

## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



R&D Manager



Technical Manager

02, 2013

---

## Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

---

---

### Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---

Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire  
AL7 1BQ  
United Kingdom  
Phone +44 1707 394444  
Telefax +44 1707 329129  
[www.sika.co.uk](http://www.sika.co.uk)  
email: [sales@uk.sika.com](mailto:sales@uk.sika.com)



Certificate No. EMS 4308



Certificate No. FM 12504

